

# POTOMAC SERIES

## STANDARD FEATURES

### FOUNDATION

- Poured concrete footers per plan
- Crawl space foundation per plans
- Vents per requirements
- Light with switch next to crawl space door
- 6 Mill Polyethylene vapor barrier
- Front concrete stoop, steps and side walk to end of the home
- Optional Basement available

### FLOOR SYSTEM

- #2 or better 2"x10", 2"x12" Floor joists @ 16" O.C. or "I" Joists depending on model
- *Solid wood blocking under parallel partitions*
- ¾" T&G Advantech or ¾" T&G Weyerhaeuser Gold Edge floor decking *glued and screwed* to floor joists
- *Congoleum* no-wax vinyl floors over ¼" luan underlayment in kitchen/bath/ and utility areas
- Standard 100% Nylon, stain resistant carpet with upgraded 6 lb. rebond pad
- Bruce ¾" T&G pre-finished hardwood floors in foyer

### EXTERIOR WALL

- 2"x4" Partition studding @ 16" O.C.
- 7/16" OSB Sheathing
- Solid colored vinyl siding, Twin 4/5 Straight lap or Dutch lap, Choice of Colors. Limited lifetime warranty by Certainteed
- Windows: Vinyl single hung, insulated, tilt-in bottom sash, with screens and grills
- Front door: 1-3/4" steel clad, insulated, six panel entry door, sidelights where shown
- Rear door: French (center hinge) metal insulated with tempered glass or Vinyl sliding glass door (see plans)
- Pre-formed wood sculpt polystyrene Louvered or Raised Panel shutters on front windows. Choice of colors
- Master mounting blocks provided with siding for exterior lights
- 2"x12" Headers over all exterior windows and doors
- Schlage exterior hardware package (front door is lever style)

### INSULATION

- Exterior walls insulated with R-13
- Ceilings insulated with R-30
- Crawl is insulated with R-19
- Optional basements are insulated with R-11 flame spread
- Crawl space includes water supply insulation
- Air guard package for exterior walls
- Air stopping for all penetrations

### INTERIOR

- Interior finished ceiling height 9' for 1<sup>st</sup> floors, 8' for 2<sup>nd</sup> floors
- 2x4 Partition studding @ 16" O.C.
- 1/2" Gypsum drywall *glued and field screwed*
- Colonial 6 panel interior doors
- Vinyl coated ventilated shelving in closets
- Oak handrails with painted balusters on 2 stories
- 2 ¼" Colonial casing on doors and windows
- 4 ¼" Colonial base boards on 1<sup>st</sup> floor and 3 ¼" Colonial base boards on 2<sup>nd</sup> floor
- 3 5/8" Crown molding in Living room and Dining room
- 2-piece chair rail in dining room
- White quarter round trim in all vinyl areas
- McCormick Two-Tone latex paint - flat finish (2 coats)
- McCormick Two-Tone latex paint - semi-gloss (2 coats) for Kitchen, baths and trim
- *Solid wood blocking* behind Kitchen cabinets and vanities
- *Solid wood blocking* behind all closet shelving
- Schlage interior hardware package

### ROOF SYSTEM

- Engineered Truss system at 24" O.C. with hurricane straps. Pitch per plans
- 7/16" OSB sheathing w/ plyclips between trusses
- 12" overhangs front and rear, 6" gable overhangs covered with vinyl soffit and aluminum fascia
- Certainteed XT25 year roof shingles over 15# felt with shingled ridge vent system
- One piece baked on enamel seamless aluminum gutters with downspouts and splash blocks

### HEATING AND AIR CONDITIONING

- 13 SEER Heat Pump by *American Standard* (or equivalent) with 10-year compressor warranty

### PLUMBING

- 80 gallon, quick recovery, electric energy efficient water heater if home has garden/soaking tub (50 gal. with standard tub/shower units)
- Two outside frost proof faucets
- Copper waterlines with individual shut-off under sinks and lavatories
- CPVC waterlines in Anne Arundel and Prince George's Counties
- Washer and Dryer hook-ups
- Ice water hook-up for refrigerator
- Delta, single lever or dual knob (your choice), plumbing fixture package with 4" spreads

### ELECTRICAL

- 200 Amp service panel box with ground rods (with 1 HVAC system)
- 350 Amp service panel box with ground rods (with 2 HVAC systems)
- All copper wiring
- AC/DC smoke and fire detectors
- Classic lighting package
- Overhead lighting in all bedrooms
- Two outside receptacles on ground fault interrupters
- Electric door chime at front entry
- Two Telephone and Four T.V. outlets
- Exterior lights at all exterior doors
- Recessed lights over kitchen sink and garden tub (if applicable)

### KITCHEN

- *Wellborn* Arlington Oak series kitchen cabinets with recessed oak panel doors. Choice of five stains (includes 42" wall cabinets for 9' ceilings)
- Base Lazy Susan where shown on plan
- Stainless steel double bowl sink w/ Delta, single lever, washerless faucet
- Formica Self edge laminate countertops with backsplash
- Drywalled soffit over wall cabinets or open: Your choice
- *G.E.* Vented (if on outside wall) range hood w/ two-speed fan and cooktop light
- *G.E.* Glass top self cleaning range
- *G.E.* Dishwasher w/ pot scrubber cycle
- *G.E.* Frost free side-by-side 25 c.f. Refrigerator with ice and water in the door

### BATH

- 60" one piece fiberglass tub/shower combination or shower stall with anti-scald valve where shown on plan
- Garden tubs with anti-scald valve where shown on plan
- Toto 1.6 gallon water saving china water closet
- Chrome *Delta* washerless Faucets
- *Wellborn* Arlington Oak series vanity cabinets with recessed oak panel doors and cultured marble vanity tops
- Exhaust fan in each bathroom
- Mirrors with lights over vanities
- Chrome bath accessories: towel bar and paper holder

### CUSTOMER CARE SERVICE PROGRAM

- Dedicated staff that oversees your project through the entire process
- Pre-construction meeting
- On site mechanical walk through with trades before rough in
- Pre-settlement inspection
- 3-month and 11-month post-settlement customer service follow up.



MHBR# 981